

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
20 January 2005 (20.01.2005)


PCT

(10) International Publication Number
WO 2005/005169 A1

- (51) International Patent Classification⁷: **B60C 11/03** // 115:00, 119:00
- (21) International Application Number: PCT/EP2003/007261
- (22) International Filing Date: 4 July 2003 (04.07.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicant (for all designated States except US): **PIRELLI PNEUMATICI S.p.A.** [IT/IT]; Viale Sarca, 222, I- 20126 Milano (IT).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **STEINBACH, Gunter** [DE/IT]; c/o Pirelli Pneumatici S.p.a., Viale Sarca 222, I-20126 Milano (DE).
- (74) Agents: **BOTTERO, Claudio** et al.; Porta, Checcacci & Associati S.p.A., Via Trebbia, 20, I-20135 Milano (IT).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: PAIR OF FRONT AND REAR PNEUMATIC TIRES FOR MOTORCYCLES AND METHOD OF IMPROVING THE PERFORMANCE ON BOTH WET AND DRY GROUND OF A MOTORCYCLE EQUIPPED WITH SAID PAIR



(57) Abstract: A pair of pneumatic tires (1, 101) comprises a front tire (1) and a rear tire (101) to be mounted, respectively, on a front wheel and on a rear wheel of a motorcycle, wherein the tread band (12) of the front tire (1) comprises: a) at least one circumferential groove (13) extending at the equatorial plane (X X) of the front tire (1) within a central zone (E) extending astride the equatorial plane (X-X); b) a plurality of transversal grooves (14) having an axially inner (14a) end lying within the central zone (E) of the tread band (12) and alternately extending from said central zone (E) towards axially opposite shoulder zones (F, G) of the tread band external to the central zone (E), at least some of the transversal grooves (14) being connected to the circumferential groove (13); and wherein the tread band (12) of the rear tire (101) comprises an area defining a substantially null sea/land ratio within a central zone (E) of the tread band (12) extending astride the equatorial plane (X-X) of the rear tire (101) and having a width of from about 5% to about 30% of the axial development of the tread band (12). Such a pair of pneumatic tires (1, 101) advantageously allows to improve both the performance on dry and wet ground and the kilometric yield and traction characteristics of the tires.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.